

# docker executor

## use of closed network connection

Docker image creation in CI job. Build kit enabled.

```
The push refers to repository [gitlab.example.com:5050/xxx/yyy/zzz]
10c2aa743a1a: Waiting
ce6021a72f8a: Preparing
...
d7987a0357ee: Retrying in 5 seconds
d0de3ca27f7d: Retrying in 5 seconds
...
d0de3ca27f7d: Retrying in 19 seconds
698c6cbaebf1: Retrying in 19 seconds
...
...
698c6cbaebf1: Retrying in 1 second
b30c875acc0a: Retrying in 1 second
343b0b7537a2: Waiting
write tcp 192.168.0.138:58472->192.168.0.42:5050: use of closed network
connection
Command exited with non-zero status 1
ERROR: Job failed: exit code 1
```

Gitlab's registry log file shows:

</var/log/gitlab/registry/current>

```
level=warning msg="client disconnected during blob PATCH" copied=64136
43 error="unexpected EOF" go_version=go1.16.9
level=error msg="connection reset by peer" code=CONNECTIONRESET
detail="client disconnected" error="connectionreset: connection reset
by peer" go_version=go1.16.9
```

Retrying job on the same runner also fails. Possible solution: remove cached image on runner host to force recreation of layers.

- [Error Pushing to Docker Hub, several errors: EOF, use of closed network connection, #16959](#)
- [Docker push fails with EOF in private registry 2.0 behind NGINX Proxy #16949](#)

From:

<https://niziak.spox.org/wiki/> - **niziak.spox.org**

Permanent link:

<https://niziak.spox.org/wiki/git:gitlab:runner:docker>

Last update: **2021/12/22 16:07**

