

Serial console



Serial converter

3,3V level converter 115200 8N1

1	2	3	4	5
Vcc	RX	TX	nc	GND



```
** MARVELL BOARD: RD-88F6281A LE
```

U-Boot 1.1.4 (Jun 8 2011 - 18:48:37) Marvell version: 3.4.19

U-Boot code: 00600000 -> 0067FFF0 BSS: -> 006CFEE0

Soc: 88F6281 A1 (DDR2)
CPU running @ 1200Mhz L2 running @ 400Mhz
SysClock = 400Mhz , TClock = 200Mhz

DRAM CAS Latency = 5 tRP = 5 tRAS = 18 tRCD=6
DRAM CS[0] base 0x00000000 size 256MB
DRAM Total size 256MB 16bit width

Addresses 10M - 0M are saved for the U-Boot usage.

Mem malloc Initialization (10M - 7M): Done

NAND:128 MB

Flash: 0 kB

CPU : Marvell Feroceon (Rev 1)

Kernel address is 0x4640000.

Streaming disabled

Write allocate disabled

Module 0 is RGMII

Module 1 is TDM

USB 0: host mode

PEX 0: PCI Express Root Complex Interface

PEX interface detected Link X1

Net: egiga0, egiga1 [PRIME]

Hit any key to stop autoboot: 0

From:

<https://niziak.spox.org/wiki/> - **niziak.spox.org**

Permanent link:

https://niziak.spox.org/wiki/hw:nsa310:serial_console

Last update: **2020/11/06 11:43**

