

```
apt-get install busybox-initramfs mdadm lvm2
```

# Shell

Activate LVM volumes and boot:

```
lvm vgchange -ay  
mount /dev/disc2/btrfs2 /root -o device=/dev/disc1/btrfs1  
exit
```

## /usr/share/initramfs-tools/scripts/

Each script can be called with prereqs argument.

## Issues

- If update-initramfs -k all -u generates more initramfs than installed kernels, please check content of directory /var/lib/initramfs-tools/
- **dropbear: WARNING: Invalid authorized\_keys file, remote unlocking of cryptroot via SSH won't work!**

```
◦ /usr/lib/dropbear/dropbearconvert openssh dropbear  
  /etc/ssh/ssh_host_dsa_key /etc/dropbear-  
  initramfs/dropbear_dss_host_key  
  /usr/lib/dropbear/dropbearconvert openssh dropbear  
  /etc/ssh/ssh_host_ecdsa_key /etc/dropbear-  
  initramfs/dropbear_ecdsa_host_key  
  /usr/lib/dropbear/dropbearconvert openssh dropbear  
  /etc/ssh/ssh_host_rsa_key /etc/dropbear-  
  initramfs/dropbear_rsa_host_key  
  cp ~/.ssh/authorized_keys /etc/dropbear-initramfs  
  update-initramfs -u
```

From:  
<https://niziak.spox.org/wiki/> - **niziak.spox.org**



Permanent link:  
<https://niziak.spox.org/wiki/linux:initramfs>

Last update: **2017/08/14 07:58**