

MSMTP

```
sudo apt-get install msmtp-mta
```

[/etc/msmtprc](#)

```
# Use TLS.
tls on
tls_trust_file /etc/ssl/certs/ca-certificates.crt

# Syslog logging with facility LOG_MAIL instead of the default
LOG_USER.
syslog LOG_MAIL

aliases      /etc/aliases

account      gmail1
auth         plain
host         smtp.gmail.com
port         587
user         tools@gmail.com
password     123456
from         tools@gmail.com

account      gmail2
auth         plain
host         smtp.gmail.com
port         587
user         backups@gmail.com
password     123456
from         backups@gmail.com

account default : gmail1
```

Aliases

Aliases file format:

```
short_name: full_remote_address
```

[/etc/aliases](#)

```
mailer-daemon: user@domain.org
postmaster: user@domain.org
nobody: user@domain.org
hostmaster: user@domain.org
webmaster: user@domain.org
www: user@domain.org
ftp: user@domain.org
abuse: user@domain.org
noc: user@domain.org
security: user@domain.org
```

```
backuppc: user@domain.org
postgres: user@domain.org
www-data: user@domain.org
```

```
root: user@domain.org
```

```
jenkins:      user@domain.org
user:         user@domain.org
```

```
# The default is the default email to which an email will be sent if no
match for a user is found.
default: user@domain.org
```

From:

<https://niziak.spox.org/wiki/> - **niziak.spox.org**

Permanent link:

<https://niziak.spox.org/wiki/linux:mail:msmtp>

Last update: **2020/10/20 07:19**

