

# Relay to external SMTP server

[Configure Postfix to Send Mail Using an External SMTP Server](#)

## Simple postfix configuration script

```
apt-get install postfix bsd-mailx
wget
https://raw.githubusercontent.com/Tontonjo/proxmox_toolbox/main/proxmox_tool
box.sh
bash proxmox_toolbox.sh
```

For TLS on port 465 add followin config lines:

```
postconf smtp_tls_wrappermode = yes
postconf smtp_tls_security_level = encrypt
```

## Manual configuration

```
# Specify zero or more "type:name" lookup tables. Type is a service defined
in master.cf
cloudservice@example.org      [smtp.gmail.com]:587
```

cd /etc/postfix && postmap relay\_by\_sender

[/etc/postfix/sasl\\_passwd](#)

```
[smtp.gmail.com]:587 myrealsender@gmail.com:secret_password
```

```
cd /etc/postfix && postmap sasl_passwd
sudo chown root:root /etc/postfix/sasl_passwd /etc/postfix/sasl_passwd.db
sudo chmod 0600 /etc/postfix/sasl_passwd /etc/postfix/sasl_passwd.db
```

[main.cf](#)

```
...
# A sender-dependent override for the global relayhost parameter
setting
sender_dependent_relayhost_maps = hash:/etc/postfix/relay_by_sender
smtp_sender_dependent_authentication = yes
smtp_sasl_auth_enable = yes
smtp_sasl_password_maps = hash:/etc/postfix/sasl_passwd
```

```
smtp_sasl_security_options = noanonymous
```

```
service postfix restart
```

Test email:

```
cat /etc/issue | mailx -r "cloudservice@example.org" -s "test relay"  
"destination@email.org"
```

## Issues

(SASL authentication failed; cannot authenticate to server smtp.server.org[11.22.33.44]: no mechanism available) solution: `smtp_sasl_security_options = noanonymous`

From:  
<https://niziak.spox.org/wiki/> - **niziak.spox.org**



Permanent link:  
[https://niziak.spox.org/wiki/linux:mail:postfix:relay\\_to\\_external\\_smtp](https://niziak.spox.org/wiki/linux:mail:postfix:relay_to_external_smtp)

Last update: **2023/02/13 12:52**