

# mc.ext.ini

Edit Extension file

```
[jpeg]
Type=^JPEG
Include=image

[Include/image]
Open=/usr/lib/mc/ext.d/image.sh open ALL_FORMATS
View=%view{ascii} /usr/lib/mc/ext.d/image.sh view ALL_FORMATS
```

So image.sh is called with `view ALL_FORMATS` and ENVs set to: `MC_EXT_BASENAME=IMG_0009.JPG`  
`MC_EXT_FILENAME=/home/user/IMG_0009.JPG`

but `ALL_FORMATS` is not well supported by image.sh and default handler is used:

```
case "${filetype}" in
jpeg|jpg)
    identify "${MC_EXT_FILENAME}"
    which exif >/dev/null 2>&1 && exif "${MC_EXT_FILENAME}" 2>/dev/null
    ;;
xpm)
    sxpm "${MC_EXT_FILENAME}"
    ;;
*)
    identify "${MC_EXT_FILENAME}"
    ;;
esac
```

Solution: edit extension file:

[mc.ext.ini](#)

```
[jpeg]
Type=^JPEG
Open=/usr/lib/mc/ext.d/image.sh open ALL_FORMATS
View=%view{ascii} /usr/lib/mc/ext.d/image.sh view jpeg
```

From:  
<https://niziak.spox.org/wiki/> - niziak.spox.org

Permanent link:  
<https://niziak.spox.org/wiki/linux:sw:mc:ext>

Last update: **2023/09/28 10:58**



