

# Bitbake

[BitBake User Manual](#)

## Bitbake tasks

- **fetch** If needed, make local copy of remote sources (bz2, git, svn, ...).
- **unpack** prepare source of package in work directory (bz2 - unpack, git - clone from local copy, etc)
- **patch** apply all \*.patch files from SRC\_URI
- **configure**
- **compile**
- **install**
- **package** split installed on fake sysroot files into separate packages:
  - main package or library (package\_name)
  - debugging symbols (package\_name-dbg)
  - documentation (package\_name-doc)
  - locales (package\_name-locale)
  - development headers (package\_name-dev)
- **clean**
- **cleanstate** remove output and SSTATE cache files for given package

## dependency explorer

Dependency explorer is replaced by “Task Explorer” in Yocto 3.3.1. [4.10.10 BitBake Changes](#)

- [bitbake -g -u taskexp](#)
- [Inspect DEPENDS](#)
- [How can I determine what is causing an unwanted package to be built in Yocto?](#)
- [Why is package included in Yocto rootfs?](#)
- [Yocto: How to know why a package is included?](#)

From:  
<https://niziak.spox.org/wiki/> - **niziak.spox.org**



Permanent link:  
<https://niziak.spox.org/wiki/sw:yocto:bitbake>

Last update: **2022/06/19 18:47**